

IN THE CLAIMS

Please amend the claims as follows:

Claim 1 (Withdrawn): An apparatus for air-cooling and tempering a glass sheet, comprising:

a conveying means installed to be operable from a forming zone to a cooling area and to convey a glass sheet in a high temperature state,

a plurality of upper blowing members provided in parallel along a conveying direction of glass sheet above the conveying means in the cooling area,

a plurality of lower blowing members provided in parallel along a conveying direction of glass sheet under the conveying means in the cooling area,

a plurality of air-supply boxes provided in each of the upper and lower blowing members for controlling blow/stop operations of cooling air from each of the blowing members, and

an air-supply source connected to these air-supply boxes,

wherein each of the air-supply boxes comprises a cylindrical damper having a perforated hole provided at its side, a casing for rotatably accommodating the damper and for forming an air channel only when the damper is at a predetermined rotational position, and a slide bearing provided in a space between the damper and the casing, wherein the cooling air supplied from the air-supply source can be supplied to the upper and/or lower blowing members through air channels by adjusting the rotational position of the damper.

Claim 2 (Withdrawn): The apparatus for air-cooling and tempering a glass sheet according to Claim 1, further comprising a control means for controlling the rotational position of a damper so that it

(a) stops cooling air to be blown from all of the upper and lower blowing members in the cooling area in the initial state,

(b) blows the cooling air from all of the upper and lower blowing members when the substantially whole of a conveyed glass sheet is entered in the cooling area, and

(c) sequentially stops the cooling air blown from the upper and lower blowing members located behind the glass sheet in response to the conveyance position of the glass sheet after the last glass sheet in the cooling area is passed.

Claim 3 (Withdrawn): The apparatus for air-cooling and tempering a glass sheet according to Claim 1, wherein an upper and/or lower blowing member comprises an air-nozzle swingable in the conveying direction of glass sheet.

Claim 4 (Withdrawn): The apparatus for air-cooling and tempering a glass sheet according to Claims 1, wherein the conveying means is a conveyer comprising a plurality of rollers disposed in parallel along the conveying direction of glass sheet.

Claim 5 (Withdrawn): The apparatus for air-cooling and tempering a glass sheet according to Claim 4, wherein the rollers move up and down according to the position of a glass sheet so that a curved glass sheet can be conveyed.

Claim 6 (Withdrawn): The apparatus for air-cooling and tempering a glass sheet according to Claim 1, wherein a plurality of dampers are connected via an Oldham's coupling.

Claim 7 (Withdrawn): The apparatus for air-cooling and tempering a glass sheet according to Claim 1, wherein the glass sheet is for a window glass of automobiles.

Claim 8 (Currently Amended): In a process for air-cooling and tempering a glass sheet comprising employing an apparatus for air-cooling and tempering a glass sheet, the apparatus comprising a conveying means installed to be operable from a forming zone to a cooling area and to convey a glass sheet in a high temperature state, a plurality of upper blowing members provided ~~in parallel~~ along a conveying direction of glass sheet above the conveying means in the cooling area, a plurality of lower blowing members provided ~~in parallel~~ along a conveying direction of glass sheet under the conveying means in the cooling area, a divided air-supply box provided for each of the upper and lower blowing members so as to control blow/stop of cooling-air ~~[[from]]~~ supplied to each of the upper and lower blowing members, a plurality of flow paths ~~defining elements~~ provided for connecting ~~connected to~~ each of said divided air-supply boxes with ~~and a~~ respective upper and lower blowing members ~~member~~ such that a plurality of flow paths of cooling air from each of the divided air-supply boxes are connected to the respective upper and lower blowing member, and an air-supply source connected to the divided air-supply boxes, wherein each of the divided air-supply boxes comprises a cylindrical damper therein, wherein each of the cylindrical dampers has ~~has~~ having a plurality of perforated holes ~~hole~~ provided at its side, a casing for rotatably accommodating the cylindrical damper and for forming ~~[[an]]~~ air channels ~~channel~~ between the plurality of perforated holes and a respective plurality of the flow paths only when the cylindrical damper is at a predetermined rotational position, and a slide bearing provided in a space between the cylindrical damper and the casing, wherein the cooling air supplied from the air-supply source can be supplied to at least one of the upper

and lower blowing members through air channels by adjusting the rotational position of the cylindrical damper, the process comprising:

(a) a step of adjusting the rotational position of the cylindrical dampers for stopping cooling air from all of the upper and lower blowing members in the cooling area in the initial state,

(b) a step of adjusting the rotational position of the cylindrical dampers for blowing the cooling air from all of the upper and lower blowing members when the substantially whole of a conveyed glass sheet is entered in the cooling area, and

(c) a step of sequentially adjusting the rotational position of the cylindrical dampers to stop the cooling air blown from the upper and lower blowing members located behind the glass sheet in response to the conveyance position of the glass sheet after the conveyed glass sheet in the cooling area is passed.

Claim 9 (Original): The process for air-cooling and tempering a glass sheet according to Claim 8, wherein an upper and/or lower blowing member comprises an air-nozzle swingable in the conveying direction of glass sheet.

Claim 10 (Previously Presented): The process for air-cooling and tempering a glass sheet according to Claim 8, wherein the conveying means is a conveyor comprising a plurality of rollers disposed along the conveying direction of glass sheets.

Claim 11 (Original): The process for air-cooling and tempering a glass sheet according to Claim 10, wherein the rollers move up and down according to the position of the glass sheet so that a curved glass sheet can be conveyed.

Claims 12-13 (Cancelled).

Claim 14 (Currently Amended): In a process for air-cooling and tempering a glass sheet comprising employing an apparatus for air-cooling and tempering a glass sheet, the apparatus comprising a conveying means installed to be operable from a forming zone to a cooling area and to convey a glass sheet in a high temperature state, a plurality of upper blowing members provided in parallel along a conveying direction of glass sheet above the conveying means in the cooling area, a plurality of lower blowing members provided in parallel along a conveying direction of glass sheet under the conveying means in the cooling area, a plurality of air-supply boxes provided in each of the upper and lower blowing members so as to control blow/stop of cooling-air from each of the blowing members, and an air-supply source connected to these air-supply boxes, wherein an upper and/or lower blowing member comprises an air-nozzle swingable in the conveying direction of the glass sheet to change the direction of the blowing of the cooling air in the conveying direction of the glass sheet, the process comprising:

(a) a step of stopping cooling air from all of the upper and lower blowing members in the cooling area in the initial state,

(b) a step of blowing the cooling air from all of the upper and lower blowing members when the substantially whole of a conveyed glass sheet is entered in the cooling area, wherein the cooling air is blown perpendicularly to a surface of the conveyed glass sheet by swinging the air nozzle in synchronization with the movement of the conveyed glass sheet, and

(c) a step of sequentially stopping the cooling air blown from the upper and lower blowing members located behind the glass sheet in response to the conveyance position of the glass sheet after the last glass sheet in the cooling area is passed.